


NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 1 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	

1.0 OBJECTIVE

This specification defines the performance, test quality and reliability requirement of the Micro Serial-ATA Host and Device connectors.


2.0 SCOPE

This specification is applicable to the termination characteristics of the Internal Micro SATA Connector for slim 1.8" FF HDD's family Products which provides for direct blind mate interconnection of disk drives to backplanes. Support only for internal 8.0 mm and 5.0 mm slim 1.8" FF HDD's.

3.0 GENERAL

This specification is comprised of two sections. Section 1 describes the capabilities required to enable a new smaller Micro Serial ATA. Section 2 describes the Micro SATA connector and cable assembly requirements and test procedures.

<u>Paragraph</u>	<u>Title</u>
1.0	OBJECTIVE
2.0	SCOPE
3.0	GENERAL
4.0	DEFINITIONS
5.0	PROCEDURE
5.1	Qualification
5.2	Material
5.3	Finish
5.4	Design and Construction
6.0	REFERENCE DOCUMENTS
6.1	ELECTRICAL CHARACTERISTICS
6.2	MECHANICAL CHARACTERISTICS
6.3	ENVIRONMENTAL CHARACTERISTICS
6.4	QUALITY ASSURANCE PROVISIONS

NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 2 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	

4.0 DEFINITIONS

4.1 Application

- 4.1.1 Engineering drawings
- 4.1.2 Process drawings

4.2 Military Standards

- 4.2.1 MIL-STD-202F: Test Methods for Electronic Components Parts
- 4.2.2 MIL-STS-1344A: Test Methods for Electrical Connectors
- 4.2.3 MIL-C-45662: Equipment Calibration
- 4.2.4 MIL-STD-2166: Connections, Electrical and Compliant Pin

4.3 Federal Specifications


- 4.3.1 QQ-N-290: Nickel Plating (Electrodeposited)
- 4.3.4 QQ-S-571: Solder

4.4 Other Standards and Specifications

- 4.4.1 UL94-VO: Flammability
- 4.4.2 EIA 364: Electrical Connector/Socket Test Procedures Including Environmental Classifications
- 4.4.3 Serial-ATA: Micro SATA Connector for 1.8" HDD for Revision 2.6

4.5 FCI Specifications

- 4.5.1 BUS-03-114: Capacitance Measurement
- 4.5.2 BUS-03-404: Normal Force Measurement
- 4.5.3 BUS-03-405: Insertion / Withdrawal Force Measurement
- 4.5.4 BUS-15-002/X: Nickel Plating
- 4.5.5 BUS-15-005/X: Gold in Contact Plating
- 4.5.6 BUS-19-002: Solderability
- 4.5.7 BUS-19-020: Porosity
- 4.5.8 BUS-19-040: Plating Adhesion
- 4.5.9 BUS-19-122: Solder Joint Reliability
- 4.5.10 GS-22-011: Pb-free Solder Heat Resistance Procedure – Convection Oven Flow
- 4.5.11 GS-22-012: Pb-free Solder Heat Resistance Procedure – Wave Solder

NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 3 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	

5.0 PROCEDURE

5.1 Qualification

Connectors furnished under this specification shall be capable of meeting the qualification test requirements specified herein. Unless otherwise specified, all measurements shall be performed within the following lab conditions ;

Temperature: 15 to 35°C

Relative Humidity : 20% to 80%

Atmospheric Pressure : 650mm to 800mm of Hg (86 ~106Kpa)

5.2 Material

Material for each part shall be specified herein, or equivalent. Substitute material shall meet the performance requirements of this specification.

5.2.1 Receptacle Terminal - The base material shall be phosphor-bronze strip or equivalent.

5.2.2 Plug Terminal - The base material shall be brass or equivalent.

5.2.3 Plug and Receptacle Insulator Housing - The insulators for the plug and receptacle connectors shall be molded of glass filled high performance polyplastic that is rated UL94V-0 or better in accordance with UL-94. See applicable product drawing for material.

5.2.4 Plug Hold-down Terminal – The base material shall be brass or equivalent.


5.2.5 Receptacle Hold-down Terminal – The base material shall be phosphor-bronze or brass. See applicable product drawing for material.

5.3 Finish

Plated finished for qualification components shall be as specified herein or equivalent. The plug and receptacle terminals shall be plated in the contact area to the minimum gold plating or palladium nickel with gold flash plating thickness specified on product prints (over 1.27µm [50µ"] minimum nickel underplate). The plug and receptacle terminal soldertail sections shall be plated with 1.91µm [75µ"] pure-tin (lead-free) minimum as specified on product prints (over 1.27µm [50µ"] nickel minimum underplate). The plug and receptacle press fit area shall be plated with 0.5µm ~ 1.5µm [60µ"] maximum pure tin (over 1.27µm [50µ"] nickel minimum underplate).

Plating Coverage; 95% minimum for under and over plate.

The metal hold down terminals for the plug and receptacle connectors shall be plated with 1.91µm [75µ"] pure-tin (lead-free) minimum as specified on product prints (over 1.27µm [50µ"] minimum nickel underplate). Plating Coverage; 95% minimum for under and over plate.

NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 4 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	

5.4 Design and Construction

The plug connector shall be a multi-piece assembly having single row of contacts in the mating area which dividing into **Signal Segment (S1-S7)**, the **Power Segment (P1, P2, P5 and P6)** or either one which transition out to either surface mount style or solder style soldertail to accommodate various P.C. board thickness. The contact pattern in the mating area will have short and long terminals in a specific pattern that results in a **0.5mm (0,020")** differential between contact points in the long and short terminals. (This allows for first mate-last break capability - see respective product prints for location of short and long terminals.)


The receptacle connector shall be a multi-piece assembly having single row of contacts in the mating area which dividing into **Signal Segment (S1-S7)**, the **Power Segment (P1, P2, P5 and P6)** which transition out to a in-line or stagger through hole pattern or surface mount pad. The contact pattern in the mating area will have short and long terminals in a specific pattern that results in a **0.5mm (0.020")** differential between contact points in the long and short terminals. (This allows for first mate-last break capability – see respective product prints for location of short and long terminals.) The receptacle hold down terminal has the board retention features that secure the connector to the board in preparation for solder reflow (through-hole) or board termination (press-fit).

In addition, there is a reserved pin, **P7** that may be defined in the future as a device activity signal. Finally, there are two optional pins, **P8 and P9**, for HDD manufacturing usage.

A special power segment key is located between pins **P7** and **P8**. This feature prevents miss-insertion of other Serial ATA cables.

A polarization peg (optional) on the bottom of the connector housing assures proper connector orientation during board mounting. The receptacle through hole connector and press fit connector are designed to terminate to board thickness of 1.57mm (0.062"), 2.36mm (0.093") and 3.18mm (0.125"). Visual examination of connectors to be done per EIA 364-18.

- 5.4.1 Mating. The connectors shall be capable of mating and unmating manually without the use of special tools.
- 5.4.2 Workmanship. Connectors shall be uniform in quality and shall be free from burrs, scratches, cracks, voids, chips, blisters, pin holes, sharp edges, and other defects that will adversely affect product's life or serviceability.

NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 5 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	

Mating Configuration Notes

- All pins are in a single row with 1.27mm (.050") pitch
- All ground pins in the Micro Serial ATA device plug power segment (connector pins P3 and P4) shall be bussed together on the Serial ATA device.
- The connection between the Serial ATA device ATA signal ground and power ground is vendor specific.
- The following sets of voltage pins in the Serial ATA device plug power segment shall be bussed together on the Serial ATA device:

P1 and P2 3.3V power delivery and pre-charge
P5 and P6 5V power delivery and pre-charge

6 REFERENCE DOCUMENTS

6.1 ELECTRICAL CHARACTERISTICS

6.1.1 Current Rating. The temperature rise above ambient shall not exceed 30°C at any point in the system when contact positions specified are powered at the power levels specified herein:


- a) Ambient Conditions: still air at 25°C
- b) Current Rating : 1.5A min per contact
- d) Reference : EIA 364-70A

6.1.2 Low Level Contact Resistance: The low-level contact resistance of a Serial-ATA receptacle connector mated with a Serial-ATA plug connector shall not exceed a change of 15mΩ after environmental exposure when measured in accordance with EIA 364-23. The maximum initial signal contact resistance is 30mΩ shall not be exceeded after environmental exposure when measured in accordance with EIA 364-23. The following details shall apply:

- a) Test Voltage : 20mV DC maximum at open circuit.
- b) Test Current : not to exceed 100mA.

6.1.3 Insulation Resistance: The insulation resistance of mated connectors shall not be less than 1000mΩ when measured in accordance with EIA 364-21. The following details shall apply:

- a) Test Voltage : 500V DC
- b) Preparation : The connectors shall be mated but not soldered to a PC board
- c) Electrification Time : 1 minute
- d) Point of Measurement: Between adjacent contacts.

NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 6 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	

6.1.4 Dielectric Withstanding Voltage: There shall be no evidence of arc-over, insulation breakdown, or excessive leakage current (0.5mA max) when the mated connectors are tested in accordance with EIA 364-20, method B. The following details shall apply:

- a) Test Voltage : DC 500V or AC 500V_{rms}.
- b) Test Duration : 1 minute
- c) Preparation : The connectors shall be mated but not soldered to a PC board
- d) Test Condition : 1 (760 Torr, or sea level)
- e) Points of measurement : Between adjacent contacts

6.1.5 Low Level Press-fit Interface Resistance: The interface between compliant section and plated through hole. The change in low level contact resistance shall not exceed 1.0mΩ after environmental exposure when measured in accordance with EIA 364-23. The following details shall apply:

- a) Test Voltage : 20mV DC maximum at open circuit.
- b) Test Current : not to exceed 100mA.


6.2 MECHANICAL CHARACTERISTICS

6.2.1 Mating / Unmating Force (Insertion/ Removal):

The internal Micro SATA connector and cable shall meet the requirements as defined for standard internal SATA Connector and cable assembly requirements and test procedures, with the exceptions listed below in Table.

Removal force Backplane connector	EIA-364-13 Measure the force necessary to unmate the connector assemblies at a max. rate of 12.5mm per minute.	2.5 N Min. after 500 cycles.
Insertion force Cabled power connector (non-latching)	EIA-364-13 Measure the force necessary to mate the connector assemblies at a max. rate of 12.5mm per minute.	45 N Max.
Removal force Cabled power connector (non-latching)	EIA-364-13 Measure the force necessary to unmate the connector assemblies at a max. rate of 12.5mm per minute.	10 N Min. for cycles 1 through 5 8 N Min. through 50 cycles

- a) Cross Head Speed: max. rate 12.5mm per minute
- b) Utilise free floating fixtures

NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 7 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	

6.2.2 Durability. EIA 364-09C

- a) Number of Cycles :Device / Host Connectors : 500 cycles
Internal Cabled Connector : 50 cycles
- b) Cycling Rates: Maximum 200 cycles/hour
- c) Preconditioning Cycles : Device / Host connectors : 50 cycles
Cabled Connector : 20 cycles
- d) No physical damage shall be observed

6.2.3 Contact Retention: Individual contacts (signal and hold down terminal) in the plug and receptacle housing shall withstand an axial load of 1.1 lbs (500 grams) minimum applied at a rate of 0.20 inches/minute without dislodging from the housing cavity.

Reference: EIA 364-29B

6.2.4 Normal force: The contact normal force shall not be less than 60 grams (nor greater than 200 grams) when tested in accordance with FCI test specification BUS-03-404.


6.2.5 Individual Pin Insertion / Retention Force : The force required to insert an individual compliant pin into a plated through hole in a printed circuit board at a rate of 5mm/ 0.2 inches per minute shall not exceed 50N. The retention force in the axial direction opposite that of insertion shall not be less than 5N.

6.2.6 PCB Hole Deformation Radius: Cross-section parallel to board surface. Photograph and measure hole deformation (deformation on board material) radius at a point 0.25 mm/ 0.010" from the surface and at the center of the compliant pin section. Include 10 holes. The minimum average (of 10 holes) hole deformation radius shall be no greater than 37,5um/ 0.0015" when measured from the drilled hole. The absolute maximum deformation radius shall not exceed 50um/ 0.002".

Reference MIL-STD-2166.

6.2.7 PCB Hole Wall Damage: Cross-section perpendicular to board surface and through the compliant section wear track. Photograph and measure the copper thickness remaining between the compliant section and the printed wiring board laminate. Include 10 holes. The minimum average (of 10 holes) copper thickness remaining between the compliant pin and the printed Wiring board laminate shall not be less than 7.5um/ 0.0003". In addition, there shall be no copper cracks separations between conductive interfaces, or laminate-to-copper separations.

Reference MIL- STD-2166.

NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 8 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	

6.3 ENVIRONMENTAL CHARACTERISTICS

After exposure to the following environmental conditions in accordance with the specified test procedures and/or details, the product shall show no physical damage and shall meet the electrical and mechanical requirements per paragraphs 6.0 and 7.0 as specified in Table 1 test sequence. Product subjected to these environmental tests must be applied to printed circuit boards. Unless otherwise specified, the assemblies shall be mated during exposure.

6.3.1 Thermal Shock. EIA 364-32, Test Condition I

- a) Number of cycles: 10
- b) Temperature Range : Between - 55°C +0/-3°C and +85°C +3/-0°C
- c) Time at Each Temperature : 30 minutes
- d) Transfer Time : 5 minutes, maximum

6.3.2 Humidity-Temperature Cycling. EIA 364-31, Method II, Test Condition A

- a) Duration of Cycles : 96 hours
- b) Relative Humidity : 90% ~ 95%
- c) Temperature Range : +40°C ± 2°C

6.3.3 High Temperature Life. EIA 364-17, Test Condition III, Method A


- a) Test Duration : 500 hours
- b) Temperature : +85°C ± 2°C

6.3.4 Industrial Mixed Flowing Gas (IMFG). EIA 364-65, Class II A

- a) Temperature : 30°C ± 1°C, 70± 2% RH
- b) Gas Concentration : Cl₂ 10±3ppb, NO₂ 200±50ppb, H₂S 10±5ppb, SO₂ 100±20ppb
- c) Half of the samples are exposed unmated for seven days, then mated for remaining seven days. Other half of the samples are mated during entire testing.

6.3.5 Physical Shock. EIA 364 - 27, Test Condition H

- a) Condition: H (294 m/s² 30G, 11 msec, half-sine)
- b) Shocks: 3 shocks in both direction along each of three orthogonal axes (18 total)
- c) Mounting: Rigidly mount assemblies
- d) No discontinuities greater than 1 µs and no physical damage observed.
- e) Free from any defect such as break, deformation, loosing and falling off etc. on each portion of the connector.

NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 9 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	

6.3.6 Vibration (Random Vibration). EIA 364 - 28, Test Condition V, Letter A

- a) Test Condition : Random 50 Hz - 2000 Hz, 5.35 g's RMS overall
- b) Duration : 30 minutes per axis
- c) Direction : each of 3 orthogonal axis
- d) Power Spectral Density : 0.02G²/Hz
- e) Mounting : Rigidly mount assemblies.
- f) No discontinuities greater than 1 μs

6.3.7 Solderability. JIS C 0050 or ANSI-J-002 Test Condition A

- a) Pre-heating : +150°C ± 10°C, 60 ~ 120 sec
- b) Soldering : 215°C ± 5°C MIN, 10 ± 1 sec
- c) Solder paste to be used is JIS Z 3282 H60A or H63A. Soldering particle is more than 200 mesh. Flux used shall be from Inactive Rosin family
- d) Acceptable Wet Solder Coverage: 95% minimum

6.3.8 Resistance to Soldering Heat. EIA 364-56

For Reflow Solder:

- a) Preheating : 100°C ~ 150°C , 60 seconds MAX
- b) Soldering : 210°C MIN , 60 seconds MAX
- c) The temperature shall be measured at contact terminal portion and the peak temperature on the upper surface of printed circuit board shall be less than 240°C


6.3.9 Solderability (Lead-Free)

- a) Pre-heating: +150°C ± 10°C, 60 ~ 120 sec
- b) Soldering: 230°C ± 5°C MIN, 10 ± 1 sec
- c) Solder paste to be used is JIS Z 3282 H60A or H63A. Soldering particle is more than 200 mesh. Flux used shall be from Inactive Rosin family
- d) Acceptable Wet Solder Coverage: 95% minimum

6.3.10 Resistance to Soldering Heat (Lead-Free)

For reflow Solder:

- a) Pre-heating: +150°C ~ 200°C, 60 ~ 180 sec
- b) Soldering: 230°C min. 60 sec max.
- c) Peak Temperature : 260°C ± 5°C MIN, 10 ± 1 sec
- d) Number of times : 3 times
- e) Reference : GS-22-011 Peak Reflow – 260 °C

NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 10 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	

For Dip and Wave Solder :

- a) Test Temperature : 260°C ± 5°C, 5 ~ 10 sec ± 1 sec
- b) Reference : GS-22-012

6.3.11 Whisker Test (Lead-Free)

Thermal Shock

- a) Temperature Range : -35°C to +125°C
- b) Time at Temperature : Min. 7 minutes
- c) Time Duration : 500 cycles ±4 cycles

Humidity Steady State:

- a) Temperature : +85°C
- b) Relative Humidity : 95%
- c) Test Duration : 500 hours ± 4 hours

6.3.11 Whisker Test (Lead-Free)

No whisker growth greater than 50 µm

6.3.12 Moisture Sensitivity Testing (For lead free SMT)

Baking :

- a) Temperature Range : +125°C±5°C
- b) Time Duration : 24 hours ± 2 hours


Humidification :

- a) Temperature : +85°C
- b) Relative Humidity : 85%
- c) Test Duration : 168 hours ± 4 hours

Reflow Soldering :

- a) Pre-heating : 150°C ~ 200°C, 60 ~ 180 sec
- b) Soldering : 217°C min. 60 ~ 150 sec
- c) Peak Temperature (at solder joint) : 260°C , 10±1 sec
- d) Number of times : 3 times

Reference GS-19-027

NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 11 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	

6.4 QUALITY ASSUANCE PROVISIONS

6.4.1 Equipment Calibration:

All test equipment and inspection facilities used in the performance of any test shall be maintained in a calibration system in accordance with MIL-C-45662 and ISO 9000.

6.4.2 Inspection Condition:

Unless otherwise specified herein, all inspections shall be performed under the following ambient conditions:

- a) Temperature : 25 ± 5°C
- b) Relative Humidity : 30% ~ 60%
- c) Barometric Pressure: Local ambient

6.4.3 Sample Quantity and Description


The numbers of samples to be tested in each group shown in Table 1 are defined as follows:

6.4.4 Groups 1 through 12

5 samples in each group: All samples must be free of defects that would impair normal connector operation. All samples must meet dimensional requirements of connector.

6.4.5 Acceptance:

- a) Electrical and mechanical requirements placed on test samples as indicated in Paragraphs 6.0 and 7.0 shall be established from test data using appropriate statistical techniques or shall otherwise be customer specified, and all samples tested in accordance with this product specification shall meet the stated requirements.
- b) Failures attributed to equipment, test setup, or operator error shall not disqualify the product. If product failure occurs, corrective actions shall not disqualify the product. If product failure occurs, corrective action shall be taken and samples resubmitted for qualification.

NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 12 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	

6.4.6 Qualification Testing:

Qualification testing shall be performed on sample units produced with equipment and procedures normally used in production. The test sequence shall be as shown in Table 1.

Visual Examination: EIA 364-18

6.4.7 Requalification Testing:

If any of the following conditions occur, the responsible product engineer shall initiate requalification testing consisting of all applicable parts of the qualification test matrix Table 1.

- a) A significant design change is made to the existing product which impacts the product form, fit or function. Examples of significant changes shall include, but not be limited to, changes in the plating material composition or thickness, contact force, contact surface geometry, insulator design, contact base material, or contact lubrication requirements.
- b) A significant change is made to the manufacturing process, which impacts the product form, fit or function.
- c) A significant event occurs during production or end use requiring corrective action to be taken relative to the product design or manufacturing process.


NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 13 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	


Table 1 Qualification Testing Matrix

TEST GROUP													
		1	2	3	4	5	6	7	8	9	10	11	12
TEST OR EXAMINATION	PARA												
Examination of Product(s)	5.4	1, 5	1, 9	1, 8	1, 8	1, 7	1, 3	1,3	1,5,8	1	1,3	1,3	1,3
Low Level Contact Resistance	6.2	2(a), 4	3(a), 7	2(a), 4, 6		4(a), 6							
Insulation Resistance	6.3				2, 6								
Dielectric Withstanding Voltage	6.4				3, 7								
Current Rating	6.1			7									
Low Level Press Fit Interface Resistance	6.5	2(b)*	3(b)*	2(b)*		4(b)*							
Mating (Insertion) Force	7.1		2										
Unmating (Removal) Force	7.1		8										
Durability	7.2	3											
Thermal Shock	8.1				4								
Humidity, Temperature Cycling	8.2				5								
High Temperature Life	8.3			3					4				
Industrial Mixed Flowing Gas	8.4					3							
Physical Shock	8.5		6										
Vibration	8.6		5										
Solderability	8.7						2						
Resistance to Soldering Heat	8.8							2					
Durability (Pre-Condition)	7.2		4			2							
Reseating (manually unplug/plug three times)				5		5							
Contact Retention	7.3								3,7				
Normal Force	7.4								2,6				
Insertion Force (Press Fit Only)	7.5									2,4,6			
Retention Force (Press Fit Only)	7.5									3,5,7			
PCB Hole Deformation Radius	7.6									8			
PCB Hole Wall Damage	7.7									9			
Solderability (Lead Free)	8.9										2		
Resistance to Soldering Heat (Lead Free)	8.10											2	
Whisker Test	8.11												2

* Press Fit Connector

7.0 NOTES

Not Applicable.

NUMBER GS-12-494	TYPE PRODUCT SPECIFICATION		
Micro Serial-ATA Connector		PAGE 14 of 14	REVISION A
		AUTHORIZED BY SL LIM	DATE 05 SEP 2007
		CLASSIFICATION UNRESTRICTED	

8.0 RECORD RETENTION (If Applicable)

REVISION RECORD

REV	PAGE	DESCRIPTION	ECR#	DATE
A	All	Released	S07-0290	05 September 2007